



TECHNICAL DATA SHEET

PRODUCT SPECIFICATION	
Width	190mm
Length	1820mm
Pack Size	2.075m ²
Planks per Pack	6 Planks (made up of some shorter boards)
Pack Weight	20kg
Total Thickness	±14mm nominal
Surface Coating	High Performance UV Cured Acrylic Lacquer
Surface Treatment	Brushed Matt Finish

PHYSICAL PROPERTY	TEST METHOD	NATURE'S OAK
Construction		3 layers
Top Layer		±2.5mm nominal
Colours in Range		12 designs
Edge Detail		Micro-Bevel 2 sides
Grading	Internal (Vibrant)	Unlimited knots ≤ 80mm (EN1310)
Colour Variation		High
Installation Method		Floating or glue down
Joining System		Uniclic® 4 sides
Moisture Content		6% - 8% MC
Slip Resistance	AS 4586:2013	P3
Abrasion Group	DIN 68861	>550
Fire Resistance	ASISO 9239.1-2003	4.6 Kw/m ² Smoke 13%
Thermal Resistance		R = 0.147
Electric Behavior		Static free
Indoor Air Quality - VOC	EN 717.1	=.02mg/m ³ (<0.124mg/m ³) E1 large chamber
Warranty	Domestic Use	20-year wear and lifetime structural*
	Commercial Use	Available upon request*

*Warranty Details

Nature's Oak Flooring Warranty Terms and Conditions are available online at www.premiumfloors.com.au (in Australia) or www.floorscape.co.nz (in New Zealand) or from an authorised Nature's Oak Retailer.