





## TECHNICAL DATA SHEET

PRODUCT SPECIFICATION	
Width	145mm
Length	580mm
Pack Size	1.009m <sup>2</sup>
Planks per Pack	12 Planks
Pack Weight	10.5kg
Total Thickness	14mm nominal
Surface Coating	High Performance UV Cured Acrylic Lacquer
Surface Treatment	Brushed Matt Finish

PHYSICAL PROPERTY	TEST METHOD	NATURE'S OAK HERRINGBONE
Construction		3 layers
Top Layer		2.5mm nominal
Colours in Range		4 designs
Edge Detail		No bevel
Grading	Internal (Vibrant)	Unlimited knots ≤ 80mm (EN1310)
Colour Variation		High
Installation Method		Glue down
Joining System		Tongue & groove
Moisture Content		6% - 8% MC
Slip Resistance	AS 4586:2013	P3
Abrasion Group	DIN 68861	>550
Fire Resistance	ASISO 9239.1-2003	4.6 Kw/m <sup>2</sup> Smoke 13%
Thermal Resistance		R = 0.147
Electric Behavior		Static free
Indoor Air Quality - VOC	EN 717.1 / ISO16000	=.02mg/m <sup>3</sup> (<0.124mg/m <sup>3</sup> ) E1 large chamber
Warranty	Domestic Use	20 year wear and lifetime structural*
	Commercial Use	Available upon request*



### \*Warranty Details

Nature's Oak Flooring Warranty Terms and Conditions are available online at [www.premiumfloors.com.au](http://www.premiumfloors.com.au) (in Australia) or [www.floorscape.co.nz](http://www.floorscape.co.nz) (in New Zealand) or from an authorised Nature's Oak Retailer.