

## TECHNICAL DATA SHEET

PRODUCT SPECIFICATION	STANDARD	EN 12104
Width		300mm
Length		910mm
Pack Size		1.638m <sup>2</sup> (6 per carton)
Pallet Size		91.728m <sup>2</sup>
Pack Weight		15kg
Total Thickness		10.5mm
Surface Treatment		Smooth UV Lacquer
Usage Class	EN 14085	Class 32 - AC4

PHYSICAL PROPERTY	TEST METHOD	READYCORK AMBIENT
Construction		Engineered Cork Flooring
Colours in Range		6
Edge Detail		Square Edge
Installation Method		Floating
Moisture Content		7% - 8% MC
Joining System		Uniclic with JointShield Sealing System
Surface Coating		High Performance UV Lacquer with Ceramic
Top Layer		3mm Cork >500Kgm <sup>3</sup>
Core		6mm High Density Fiberboard
Balancing Layer		1.5mm Cork with Microban
Slip Resistance	AS 4586:2013	P4
Abrasion Group		AC4
Fire Resistance	AS 9239.1- 2003	1.3 kwm <sup>3</sup> / Smoke 26
Thermal Resistance		R=0.10 kw/m <sup>2</sup>
Electric Behavior		Static Free
Indoor Air Quality - VOC	ASTM D5116	0.1 mg/m2/hr (24 hours)
Warranty	Domestic Use	25 year wear and lifetime structural*
	Commercial Use	Available upon request*

**\*Warranty Details**

All ReadyCork Flooring Warranty Terms and Conditions are available online at [www.premiumfloors.com.au](http://www.premiumfloors.com.au) (in Australia) or [www.floorscape.co.nz](http://www.floorscape.co.nz) (in New Zealand) or from an authorised ReadyCork Retailer.