



Technical data sheet

Product specification

Range	1-strip		Herringbone	Herringbone Grande
	gloss	matt	matt	matt
Panel size	1820 x 134mm	1820 x 134mm	580 x 134mm	610 x 165mm
Nominal thickness	±14mm	±13mm	±13mm	±13mm
Pack size m ²	1.219m ²	1.219m ²	0.933m ²	1.208m ²
Lengths per pack	5	5	12	12
Pack weight	SID1S7610 - 14.32kg SID1S7625 - 15.31kg	SID1S7629 - 14.1kg SID1S7621- 14.1kg	SIDH7615- 10.04kg SIDH7621- 10.86kg SIDH7629- 10.85g	SIDG7621- 13.97kg SIDG7629- 13.97kg
Packs per pallet	91	91	99	99
Pallet size	110.97m ²	110.97m ²	92.33m ²	119.59m ²

Panel build up

Construction	3 layers			
Top layer	±3mm	±2.5mm	±2.5mm	±2.5mm
Core board	HDF			
Backing layer	Spruce			
Joining system	Uniclic 2 sides	Uniclic 2 sides	Tongue & groove	Tongue & groove
Installation method	Floating or glue down	Floating or glue down	Glue down	Glue down

Surface layer

Wood species	Spotted Gum, Blackbutt	Spotted Gum, Blackbutt Tasmanian Oak	Spotted Gum, Blackbutt Tasmanian Oak	Spotted Gum, Blackbutt
Origin	Australia			
Grading	AS2796 standard and better All Australian timber species are graded to AS2796 Standard and Better classification. This grading embraces the natural character of Australian eucalypts, including knots, gum veins, fine checking and other distinctive natural features that contribute to the unique appearance of each floor.			
Bevel	No bevel	No bevel	4 sides	4 sides
Surface treatment	No brushing	No brushing	Light brushing	Light brushing
Finish	Gloss	Matt	Matt	Matt



Technical data sheet

Warranty

Residential warranty	25 years
Structural warranty	Lifetime
Commercial warranty	Upon request

Technical performance

Range	1-strip		Herringbone	Herringbone Grande
	gloss	matt	matt	matt
Slip resistance AS4586	P1	P3	P3	P3
Reaction to fire AS9239	CHF 4.6 kW/m ² Smoke 13%			
Emission of formaldehyde EN 717-1	≤E1			
Underfloor heating	Not suitable			
Castor chairs	Use soft castors, type W (EN 12529) and/or suitable office matt			